



interactive
anywhere,
interactive
anytime,
panelworx
delivers.

ROTATIONAL MOUNT FOR PX SERIES UNITS

PANELWORX

Safe Transportation and Easy Setup!

The RDT Case is an integration of the PX or OLX Series Displays with a mobile and durable case. For any interactive temporary application requiring touch screen interactivity, the RDT case provides a literal "out-of-box" solution.

- 32" to 55" PX or OLX Displays
- Multi-Touch Optical Touch Screen
- Durable, Impact Resistant Case
- Easy Transportable
- Rotational Bracket Included to Switch Between Portrait | Landscape Modes
- ModPlayer Integrated Module for PX Units



The RDT Case can be easily transported between locations and it is ready to go in just a few minutes



The RDT Series from PanelWorx has a durable crate that protects the panel during shipment and can then be used to mount the display making for an extremely simple set-up in just a few minutes

The RDT Series displays support the PX Series displays including an optional integrated computer and speaker system for a no hassle mobile solution.

In addition, customers can incorporate their own media player, video game console, or any other system designed to their specific needs.

Ideal for:

- Educational Training
- Event Digital Signage
- Information Kiosks
- Self-Service Kiosks
- Trade Shows
- Temporary Wayfinding

Case Features:

- Rotational Mounting Bracket for Portrait or Landscape
- Shock Mounted Monitor Frame
- Integrated Cable Management System
- Four 4" Locking Casters
- Locking 2-Piece Lid is Split for Easy Access



SPECIFICATIONS

RDT MOBILE CASE				
Exterior Size	65" High x 34" Wide x 19" Deep			
Weight	200 lbs (Display not included)			
PX SERIES DISPLAY UNITS				
SPECS	PX32	PX42	PX46	PX55
Display Size	32" LCD	42" LCD	46" LED	55" LED
Resolution	1366 x 768	1920 x 1080	1920 x 1080	1920 x 1080
Viewing Angle	H: 178°, V: 178°	H: 176°, V: 176°	H: 176°, V: 176°	H: 178°, V: 178°
Contrast Ratio	3500:1	3500:1	3000:1	4000:1
Brightness	450 cd/m2	700 cd/m2	600 cd/m2	600 cd/m2
Response Time	8 ms	8 ms	8 ms	8 ms
Aspect Ratio	16:9	16:9	16:9	16:9
Weight	75 lbs	90 lbs	105 lbs	115 lbs
Power Consumption	Approx. 175W	Approx. 250W	Approx. 275W	Approx. 375W
Touch Screen	Optical Touchscreen, 4-6 mm glass, USB Interface, fully HID compliant, Supports OS Windows, Linux, Mac			
Bulb Life	CCFT Back Life estimated to be about 50,000 hours			
Mounting Bezel	Standard black powder coat finish on rugged steel structure			
Warranty	24 Month Limited Warranty. Extended warranty available, contact us for more details			
MODPLAYER MODULE				
System	Mini-ITX ATI Fusion: 2x Ethernet RealTek 1.0Gb, 4x USB 2.0, 2x RS232 Ports, Audio In/Out, DVI, PS/2 Mini-ITX Intel CP100: Up to 8Gb DDR3, 4x USB, 2x Ethernet, 2x COM, DVI, VGA, 1x 3 Jacks Audio I/O, PS/2			
CPU	AMD Mobile Fusion, iCore i3, i5, i7			
Operating System	Windows XP Pro, Windows XP Embedded, Windows 7, Windows 7 Embedded			
Memory	2Gb to 8Gb DDR2 or DDR3			
Storage Drives	2.5" SATA Hard Drives / 2.5" Solid State Drives			
Power Supply-PC	120~240 VAC 60/100 Watt Power Supply			
Power Supply-Display	120~240 VAC 300 Watt Power Supply			
Temperature	0°~50°C (32°~122°F) Operating / -25°~60°C (-4°~140°F) Non-Operating			
Relative Humidity	20% ~ 80% Non-Condensing			
Shock	10G Operating / 15G Non-Operating			
Vibration	1.0G from 57-2000 Hz Operating / 2.5G from 57-2000 Hz Non-Operating			
Warranty	24 Month Limited Warranty. Extended Warranty Available, Contact Us For More Details			